

DATA SHEET

BSA-450

NEW! BSA-450!

Automatic cutting unit ✓

PLC controlled ✓

Standard films usable ✓



Semi-automatic twist wrapping machine for lower requirements.

Applications

All kinds of long products and profiles up to the product dimensions specified below.

Your benefit

- high efficiency
- wide range of applicability
- divergent products can be packed in bundles or entirely wrapped to convenience
- no risk of product damage
- extremely low cost of consumables and energy
- machine operating at low noise level
- no set-up times required
- PLC controlled by an HMI touch panel

Product dimensions

Width: 20 – 400 mm

Height: 20 – 250 mm

Length: 600 mm to unlimited

Maximum cross-section diagonal: 400 mm

BSA-450

Wrapping/packaging materials

Standard sizes usable
PE stretch film, VCI stretch film, PE film, crepe paper, etc.
Width: up to 125 mm
Core section: 76 mm

Specifications

Dimensions (width x depth x height): 1,100 x 1,000 x 1,500 mm
Weight: >800 kg
Control voltage: 24 VDC
Line voltage: 400 V – 50 Hz, 3-phase
Power consumption: approx. 1 kW
Noise level: <79 dB (depending on wrapping material)

Technology

- automatic clamping and cutting unit (optional)
- PLC controlled by an HMI touch panel
- easy and quick handling
- continuously variable film tension/strain
- quick-change unit for wrapping material coils

Options

Automatic clamping and cutting unit.
Second material roll holding fixture for additional packaging material, e. g. film crepe combinations.

Further features

The machines all conform to CE guidelines and have been designed using the latest technology and design criteria for industrial use.

Also available as model 1000.

(The company reserves the right to make technical changes without prior notification)

BSA-450

Views of the machinery (examples)

